DIVERSIFIED AIR SYSTEMS, INC.

INFLO-DB™

Portable Downdraft Booth

- Typical applications: Welding, Grinding, Sanding, Dust, Mist, Smoke, Powders, Lint, Fibers etc.
- Ships fully assembled, 48" wide x 24" deep work surfaces, optional 1' modular table extensions
- Plug and play unit, total self-contained downdraft booth



- Dust tight florescent light mounted out of air stream
- Recirculates clean air, which eliminates the need for expensive exhaust
- High efficiency media filters with optional refillable adsorption module and 99.97% HEPA Filter

Superior technology generating substantial operating savings



MAXFLO PORTABLE DOWNDRAFT BOOTH

Diversified Air Systems, Inc. now offers an easy to use portable downdraft booth. The MAXFLO-DB is a totally self-contained portable filtration unit. Standard filtration consist of an aluminum mesh pre-filter followed by a MERV 14 (95% at 1 micron) box filter. Separate access door allows for easy access to filters. The motor is mounted out of the air stream with direct drive spark resistant blower wheel. Florescent light, on/off switch and wiring are all located out of the airstream. Just roll the unit to your job, plug it in and turn it on.

OUTSTANDING STANDARD MAXFLO FUME BOOTH FEATURES



TYPICAL APPLICATION FOR THE MAXFLO DOWNDRAFT BOOTH


• Welding • Grinding • Sanding • Dust • Powders • Mist, Smoke, etc...

Made in USA
1 YEAR LIMITED WARRANTY

CALL TODAY: 800-264-8958

WFLO-DB™

OUTSTANDING STANDARD MAXFLO DB FEATURES





SPECIFICATIONS

Dimensions: 48" W x 39" D x 74" H

Working Table Height: 41"

Working Surface: 48" Width x 24" Depth

Electrical: 1.5 HP Motor, 120/1/60

Direct Drive Motor with Plastic Blower Wheel

Motor Mounted Out of Airstream

CFM: 1900 CFM Nominal

Downdraft Velocity: 250 FPM Nominal

Weight: 500 lbs.

Max Table Load: 300 PSF Noise: 73 DBA Nominal

Construction: 14 Gauge Cabinet

Color: Powder Coated Gray

OPTIONAL FEATURES

- Polyester Filters
- Steel Bar Grate
- Small Enclosure 30" wide x 24" deep
- HEPA Filtration
- 1 HP motor 1000 CFM Nominal
- Absorption Modules
- Modular Table Extensions

MAXFLO-FB STANDARD FILTER ARRANGEMENT

- (1) 1" Aluminum Mesh Prefilter
- (1) 95% @ 1 Micron (MERV 14) Fiberglass
 Box Filter, 58 sq. ft.

Note: Specifications listed above may be modified to suit application. contact D.A.S. or representative for information.

Diversified Air Systems, Inc.

10801 Electron Drive, Louisville, Kentucky 40299

Toll free: (800) 264-8958

Tel.: (502) 267-0333 • Fax: (502) 267-4241

Website: www.diversair.com • email: info@diversair.com